

PRODUCT DESCRIPTION

Oscar ATF CVT is a high-performance transmission oil formulated with selected base stocks and special recommended for use in latest generations of Continuously Variable Automatic Transmissions (CVT) which transfer traction via steel-made traction chains or belts. is specifically formulated for today's technologically sophisticated variable transmissions. It is formulated with premium synthetic base stocks, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers.

APPLICATION

Recommended for use in most belt and chain-driven continuously variable transmissions and will not void new car warranties. Not recommended for Hybrid CVT units (Toyota and Ford).

PROPERTIES

- Full synthetic fluid
- Excellent anti-shudder durability
- Superior wet clutch performance
- Excellent anti-wear performance
- Excellent metal-metal friction protection
- Designed to provide excellent torque transfer

PERFORMANCE LEVELS

Meets and exceeds:

- BMW Mini Cooper EZL 799 ;Dodge/Jeep NS-2, CVTF+4 ;Ford CVT23, CVT30/Motorcraft XT-7-QCFT, Mercon C ; GM/ Saturn DEX-CVT ; Honda HMMF, HCF-2 ;Hyundai/ Kia CVT applications (SP-CVT 1) ; Mazda CVTF 3320 ; Mercedes Benz 236.20 ; Mitsubishi CVTF-J1, CVTF-J4; Nissan NS-2, NS-3 ; Shell Green 1V;Subaru Lineartronic CVTF (P/N K0425Y0710), CV-30, High Torque CVTF, e-CVTF ; Suzuki TC, NS-2, CVTF 3320, CVT Green 1, CVT Green 2; Toyota TC, FE ; Volkswagen/Audi TL 52180; G 052 180, G 052 516

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	ATF CVT
Viscosity Grade			-
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.848
Viscosity @ 100°C, cSt	ASTM D445	cSt	7.5
Viscosity @ 40°C, cSt	ASTM D445	cSt	34
Viscosity Index (min)	ASTM D2270	-	175
Brookfield Viscosity @-40 °C, cP	ASTM D2983	cP	12,000
Pour Point, °C	ASTM D97	°C	-42
Flash Point, °C	ASTM D92	°C	210

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com