

PRODUCT DESCRIPTION

Oscar ATF DCT is a high-performance Multi-Vehicle Dual Clutch Transmission Fluid formulated with selected base stocks, additives and viscosity modifier technology to deliver performance enhancements compared to common genuine oils.

APPLICATION

Oscar ATF DCT can be used to service almost all passenger car wet-clutch DCTs in the global marketplace, including (but not limited to):

- VW, Seat and Skoda wet Dual Clutch Transmissions
- Audi Clutch units in Dual Clutch Transmissions
- Ford, Volvo, Mitsubishi and PSA wet Dual Clutch Transmissions
- BMW, Porsche & Mercedes-Benz wet Dual Clutch Transmissions

PROPERTIES

- Full synthetic fluid
- Superior wet clutch performance
- Excellent anti-wear performance
- Excellent metal-metal friction protection
- Designed to provide excellent torque transfer

PERFORMANCE LEVELS

Meets and exceeds:

Audi, Seat, Skoda, Volkswagen (VW TL 052 182; VW TL 052 529), BMW 1, 3, 5, 6 series, Z4, X1 (BMW DCTF-1), Peugeot/Citroen 9734.S2, Ferrari TF DCT-F3, Fiat BOT 341, Ford/Nissan M2C936A (BOT 341), Mercedes-Benz A-Class, B-Class (MB 236.21; MB 236.25), Mitsubishi MZ320065 Dia-Queen SSTF-I, Porsche (ZF) Boxster, Cayman, 911, Panamera, Renault Getrag (BOT 450), Volvo C30, S40, S60, V40, V50, V60, V70 S80, XC30, XC60 (1161838 1161839)

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	ATF DCT
Viscosity Grade			-
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.845
Viscosity @ 100°C, cSt	ASTM D445	cSt	7.3
Viscosity @ 40°C, cSt	ASTM D445	cSt	33.8
Viscosity Index (min)	ASTM D2270	-	185
Brookfield Viscosity @-40 °C, cP	ASTM D2983	cP	12,000
Pour Point, °C	ASTM D97	°C	-42
Flash Point, °C	ASTM D92	°C	200

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com