

## PRODUCT DESCRIPTION

Oscar TFX SAE 75W90 API GL-4/GL-5 is a fully synthetic universal all season gear lubricant formulated from synthetic base oils and an advanced additive system.

## APPLICATION

Oscar TFX SAE 75W90 API GL-4/GL-5 provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and transaxle startup, and also maintains a thick protective oil film during extremely hot operating conditions. Used in powered transmission and axle drives for cars, highway light and heavy-duty trucks, busses, and vans where an API GL-4/GL-5 is required.

## PROPERTIES

- Exceptional thermal stability
- Enhanced frictional properties
- Resistance to high temperature oxidation
- Outstanding protection against low speed/high torque wear

## PERFORMANCE LEVELS

Meets and exceeds:

API GL-4/GL-5; API MT-1 ; SAE J2360; MIL L 2105 D/PRF 2105 E ; EATON Europe; MAN 341 Z2; MAN 341 S1; MB 235.8; MERITOR O-76-N; SCANIA STO 1:0; VOLVO 97312 ; ZF TE-ML 02B ; ZF TE-ML 12L ; ZF TE-ML 12N ; ZF TE-ML 19C

## TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	Oscar TFX SAE 75W90
Viscosity Grade			75W90
Density @ 15°C, kg/l	ASTM D1298	kg/l	0.860
Viscosity @ 100°C, cSt	ASTM D445	cSt	15.7
Viscosity @ 40°C, cSt	ASTM D445	cSt	115
Viscosity Index (min)	ASTM D2270	-	144
Pour Point, °C	ASTM D97	°C	-45
Flash Point, °C	ASTM D92	°C	210

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.oscarlubricants.com](http://www.oscarlubricants.com)